



TABLE 1:

N	A	B	C
4	1.5	2.6	5.0
5	2.0	3.1	5.5
6	2.5	3.6	6.0
7	3.0	4.1	6.5
8	3.5	4.6	7.0
9	4.0	5.1	7.5
10	4.5	5.6	8.0
11	5.0	6.1	8.5
12	5.5	6.6	9.0
13	6.0	7.1	9.5
14	6.5	7.6	10.0
15	7.0	8.1	10.5
16	7.5	8.6	11.0
17	8.0	9.1	11.5
18	8.5	9.6	12.0
19	9.0	10.1	12.5
20	9.5	10.6	13.0
21	10.0	11.1	13.5
22	10.5	11.6	14.0
23	11.0	12.1	14.5
24	11.5	12.6	15.0
25	12.0	13.1	15.5
26	12.5	13.6	16.0
27	13.0	14.1	16.5
28	13.5	14.6	17.0
29	14.0	15.1	17.5
30	14.5	15.6	18.0
31	15.0	16.1	18.5
32	15.5	16.6	19.0
33	16.0	17.1	19.5
34	16.5	17.6	20.0
35	17.0	18.1	20.5
31	17.5	18.6	21.0
32	18.0	19.1	21.5
33	18.5	19.6	22.0
34	19.0	20.1	22.5
35	19.5	20.6	23.0

TABLE 2:

Z	Y	材 质
1	A	PA 46
2	B	LCP
3	C	PA 9T

TABLE 1:

Y	材 质
A	PA 46
B	LCP
C	PA 9T

额定电流 Current rating: 0.4A

额定电压 Voltage rating: 50V

耐压 Withstand voltage: 200V AC/minute

接触电阻 Contact resistance: $\square 20m\Omega$

绝缘电阻 Insulation resistance: 500M Ω

工作温度 Working temperature: -20° c ~ +80° c

BOM 表:

序号	品 名	料 号	材料规格	电镀方式/颜色	使用数量	备 注
3	0.5mm间距D型无锁立式贴片反向-焊片	FPC050D014-3	Phosphorbronze T=0.30MM	镀锡	2 PCS	
2	0.5mm间距D型无锁立式贴片反向-PIN	FPC050D014-2	Phosphorbronze T=0.20MM	镀锡	—	
1	0.5mm间距D型无锁立式贴片反向-基座	FPC050D014-1NY	SEE TABLE SEE TABLE 1	—	1 PCS	

F



浙江紫瑞电子有限公司
ZHEJIANG ZIRUI ELECTRONIC CO., LTD

DRAWN BY XINGCUI HU

CHECKED BY MEIJIAO LONG

ITEM 0.5mm间距D型无锁立式贴片反向
(0.5-B-nPPBS)

ANGLE PROTECTION

SCALE 1:1

新订图面

F

APPROVED BY JIYAO HU

PART NO

ZR6. 602. 063

TOLERANCE .x±0.2
.xx±0.10

DATE 2010/03/31

REVISION

DESCRIPTION

DATE

F

1

2

3

4

5

6

7

8

F